



Technical Specifications

Battery Charger:	Class 2, Power Supply
Plug:	AC/DC Adapter Wall Plug
Battery Type/Fit:	NiMH: 1-4 AA/HR6, 1-4 AAA/HR03, 1-4 C/HR14, 1-4 D/HR20, 9V
Typical Weight:	330.5 g
Input:	100-240V AC, 50/60 Hz, 7.2W
Output:	1-2 AA/2C/2D 1350 mA, 1-2AAA 750 mA, 3-4 AA/AAA/C/D 750 mA, 9V 32 mA
Operating Temp:	0°C - 35°C (32°F - 95°F)
Dimensions:	156 mm (H) x 101 mm (W) x 59 mm (D)

BENEFITS

Simple & Easy to Use “All-In-One” Charger for Multiple battery Sizes
2 AA ready in 1 hr.*

FEATURES

Charges AA, AAA, C, D, 9V NiMH batteries – LED Indicates Charge Status

- RED LED for AA, AAA, C, D, 9V
- Charges up to 4 batteries
- Charges multiple sizes

LED Indicates Charge

- Solid Red = Charging
- Green = Complete
- Blinking Red = Error/Abnormal battery or abnormal temperature

Charger Automatically detects battery sizes at the same time

International Charge Capability – device can be used worldwide with suitable converter plug

SAFETY

Microprocessor Controlled

- Charge Termination based on – dV/dt, temperature, and/or built in timer
- Primary Battery Protection – will not charge non-rechargeable batteries
- Over-temperature shut off – prevents overheat of battery
- Over-charge protection – prevents battery damage
- Low-voltage battery protection – prevents overheat and damage to battery
- Power protection circuit – resets whenever a battery is removed

DURACELL®
BATTERIES

Berkshire Corporate Park
Bethel, CT 06801 U.S.A.
Tel: Toll free 1.800.544.5454
Web: www.Duracell.com

*Approx. 85% of full charge, when using Duracell AA1300 mAh NiMH Batteries.

Information and contents in this data sheet are for reference purposes only. They do not constitute any warranty and representation is subject to change without prior notice. For most current information and further details, please contact Duracell.